



TIANJIN GREWIN TECHNOLOGY CO.,LTD.

Web:www.grewin-tech.com WhatsApp:+86-13072088960

Email:salesmanager@grewin-tech.com

Transformer For Audio Technology



Item No.	Rated Power (VA)	Voltage Regulation(%)	Efficiency (%)	Dimension(mm)		Weight (Kg)
				Height	Diameter	
GWBT-10	10	19.8	75	13	55	0.22
GWBT-15	15	19.8	75.5	15	60	0.28
GWBT-20	20	19.5	76	20	65	0.33
GWBT-25	25	19.5	78	25	67	0.38
GWBT-30	30	16.8	79.5	25	70	0.49
GWBT-40	40	15.7	81.5	35	75	0.58
GWBT-50	50	15	83	35	78	0.68
GWBT-60	60	13.4	85	35	90	0.77
GWBT-80	80	12.3	85.5	35	93	0.97
GWBT-100	100	11	88.2	36	103	1.25
GWBT-120	120	9.5	88.6	38	108	1.58
GWBT-140	140	6.8	88.8	43	115	1.95
GWBT-160	160	6.4	89	45	117	2.05
GWBT-180	180	6.4	89.2	46	118	2.2
GWBT-200	200	6	89.9	48	118	2.35
GWBT-250	250	5.3	90.45	51	126	2.88
GWBT-300	300	5.1	92	54	126	3.15
GWBT-350	350	5.1	92.2	56	130	4.2
GWBT-400	400	4.4	94	68	135	4.5
GWBT-500	500	4.1	94.8	70	141	5.3
GWBT-800	800	3.7	95.3	73	168	8.15
GWBT-1000	1000	3.4	96.2	76	178	9.985
GWBT-1200	1200	2.8	96.8	80	195	13.38
GWBT-1400	1400	2.8	96.8	83	200	14.5
GWBT-1600	1600	2.7	97	85	208	15.93
GWBT-2000	2000	2.4	97.5	88	235	19.98
GWBT-5000	5000	2.2	98	90	242	25.53



Grewin

TIANJIN GREWIN TECHNOLOGY CO.,LTD.

Web:www.grewin-tech.com WhatsApp:+86-13072088960

Email:salesmanager@grewin-tech.com

Features:

1. Especially low-hum and low-dispersing construction, Low-level of induction
High-grade design casing possible,Statically shield winding and magnetical shield winding optional.
2. Low noise transformer designs will meet your audio needs.
3. In an audio application, unfiltered noise or unwarranted harmonic distortions can produce signal spikes that will affect the overall sound quality. Our unique Quiet designs will provide a long term solution for your audio needs, while not sacrificing overall size and cost.
4. More than ten years experience in this industry, our engineers will work closely with your team and develop the best solution for your audio application.

General Data:

- 1.Rated input voltage 230 Vac
- 2.Rated output voltage 2 x 12 - 2 x 35 Vac
- 3.Power 15 - 625 VA
- 4.Insulation class B
- 5.Maximum ambient temperature 40 °C
- 6.Efficiency up to 95 %
- 7.Degree of protection IP 00

Advantages:

- 1.Minimum size at high output
- 2.Low weight
- 3.Double output voltage for series or parallel connection
- 4.Protected against overload by integral temperature fuse
- 5.Minimal no-load losses
- 6.Outstanding temperature behaviour thanks to low magnetic leakage field
- 7.Very low noise field

Application:

Power amplifier / Line Level Preamplifier / Acoustic Monitor / Power Conditioner
Aktive subwoofer / UniField Speaker / Loudspeaker / Center speaker
Powered subwoofer system / Indoor Or Outdoor Bookshelf Speakers / Home audio
Receivers / Theater amplifiers / Zone amplifiers / Multi-room amplifiers / Network
amplifiers / Art speakers